


CHAPTER-13
PLASTER AND POINTING

Sl. No.	DESCRIPTION OF ITEMS	UNIT	Jalaun	Jhansi	Lalitpur
1	2	3	4	5	6
17.58	12 mm Cement plaster in single coat on fair side of single or half brick wall for interior plastering upto floor two level including internal rounded angles chamfers, and/or rounded angles not exceeding 80 mm. In girth and finished even and smooth. No extra for mixing any additive.				
	(I) 1 Cement : 3 Coarse sand	Sqm.	170.90	166.90	174.80
	(II) 1 Cement : 4 fine sand	Sqm.	144.20	140.20	148.10
	(III) 1 Cement : 6 fine sand	Sqm.	130.10	126.10	134.10
17.59	15 mm Cement plaster in single coat on rough side of single or half brick wall for interior plastering upto floor two level including internal rounded angles chamfers, and rounded angles not exceeding 80 mm. In girth and finished even and smooth.				
	(I) 1 Cement : 3 Coarse sand	Sqm.	213.60	208.60	218.50
	(II) 1 Cement : 4 fine sand	Sqm.	180.30	175.30	185.10
	(III) 1 Cement : 6 fine sand	Sqm.	162.60	157.60	167.60
574	Struck cement pointing above but with cement mortar consisting of one part of cement and two part of Fine sand of 1.25 Fm.	Sqm.	163.10	162.40	163.90
574a	Struck cement pointing above but with cement mortar consisting of one part of cement and two part of Coarse sand of 2.20 Fm.	Sqm.	165.10	164.40	165.90
575	As in item no. 574 above but flush pointing deduct form item 574.	Sqm.	22.80	22.80	22.80
576	As in item 574 and 575 above but in floors deduct from item 574 and 575	Sqm.	25.50	25.50	25.50
577	Raised pointing with cement and Fine sand 1.25 F.M. mortar on brick work in proportion of 1 :2, including supply of all material, labour and T & P etc. required for proper completion of the work	Sqm.	143.40	142.40	144.40
577a	Raised pointing with cement and coarse sand 2.20 F.M. mortar on brick work in proportion of 1 :2, including supply of all material, labour and T & P etc. required for proper completion of the work	Sqm.	145.40	144.40	146.40
578	Struck cement pointing 1:2 with colouring materials to match the brick work colour including supply of all material , labour & T&P etc. required for proper completion of the Work.	Sqm.	164.50	163.50	165.60
596	Add for extra labour and material for plaster over rough face of one brick walls.	Sqm.	15.30	15.30	15.30

S.E.T.

Sl. No.	DESCRIPTION OF ITEMS	UNIT	Jalaun	Jhansi	Lalitpur
597	2 cm.(3/4") thick cement plaster in dedo or skirting in 1:2 consisting of one part of cement and 2 parts of approved coarse sand laid in panels. finished with 3 mm.(1/8"). floating, coat of neat cement or cement and marble dust in ratio 5:1 including supply of materials labour and T&P etc. required for proper completion of the work.	Sqm.	231.40	225.90	236.30
598	Engraving lines in the plaster of outer face wall vertically and horizontally to display the surface as stone facing as directed by Engineer-in- charge including labour & T&P etc. required for proper completion of work.	Sqm.	32.00	32.00	32.00
599	Providing and fixing water proofing material in cement mortar for plastering or in concrete work in the proportion recommended by the manufacturer.	Sqm.	21.90	21.90	21.90


 (Er. Shripal Singh)
 Superintending Engineer
 Jhansi Office, P.W.D., Jhansi
 22.07.2014
 S.E.O.