

<b>Chapter 13</b>
<b>PLASTER AND POINTING</b>

S.No.	Sch. PWD	Item No. NBO	Description of item	P.W.D. Spec. No.	Unit	Effective Rate
1	<b>574</b>		<b>Pointing</b> Struck painting on brick works with cement mortar in 1:2 with consisting of one part cement & two parts of fine sand of 1.25 F.M. including supply of all materials, labour & T & P etc required for proper completion of the work.		Sqm.	185.00
2	<b>575</b>		As in item no. 574 above but for flush pointing deduct form item 574		Sqm.	(-)20.00
3	<b>576</b>		As in item no. 574 and 575 above but for flush deduct form item 574 and 575.		Sqm.	(-)23.00
4	<b>577</b>		Raised pointing with cement and fine sand of 1.25 F.M. mortar on brick works in proportion of 1:2, including supply of all materials labour and T&P etc. required for proper completion of the work		Sqm.	152.00
5	<b>578</b>		Struck cement pointing 1:2 with colouring materials to match the brick work colour including supply of all materials, labour and T & P etc. required for proper completion of the work. Racking and washing surface.		Sqm.	140.00
6	<b>580</b>		<b>Plaster</b> 12mm. Thick plaster with cement mortar in proportion of 1:2 cement & fine sand of 1.25 F.M.		Sqm.	161.00
7	<b>581</b>		As in item 580 above but with cement mortar in proportion of 1:2 consisting one part cement and two parts of approved coarse sand.		Sqm.	192.00
8	<b>582</b>		As in item 580 above but with cement and fine sand of 1.25 F.M. mortar in 1:3.		Sqm.	139.00
9	<b>583</b>		As in item 580 above but with cement and approved coarse sand in 1:3.		Sqm.	156.00
10	<b>584</b>		As in item 580 above but with cement and fine sand of 1.25 F.M. mortar in 1:4.		Sqm.	126.00
	<b>584(B)</b>		As in item 580 above but with cement and coarse sand		Sqm.	141.00
11	<b>586</b>		As in item 580 above but with cement and fine sand of 1.25 F.M. mortar in 1:6.		Sqm.	111.00
12	<b>587</b>		Add for extra labour to all items of plaster if done in ceiling.		Sqm.	11.00
13	<b>597</b>		2 cm (3/4") thick cement plaster in dedo or skirting in 1:2 consisting of one part of cement and 2 parts of approved coarse sand laid in panels, finished with 3 mm (1/8") floating coat of neat cement or cement and marble dust in ratio of 5:1 including supply of all materials, labour and T&P etc. required for proper completion of the work.		Sqm.	216.00
14	<b>598</b>		Engraving lines in the plaster of outer face well vertically and horizontally to display the surface as stone facing as directed by the Engineer-in-charge including labour & T&P etc. required for proper completion of the work. Add for extra labour to all items of plaster.		Sqm.	21.20

**(Gyan Prakash Pandey)**  
 Superintending Engineer  
 Azamgarh Circle, P.W.D.,  
 Azamgarh