

Chapter 13						
PLASTER AND POINTING						

S.No.	Sch. PWD	Item No. NBO	Description of item	P.W.D. Spec. No.	Unit	Effective Rate
1	574		Pointing Struck painting on brick works with cement mortar in 1:2 with consisting of one part cement & two parts of fine sand of 1.25 F.M. including supply of all materials, labour & T & P etc required for proper completion of the work.		Sqm.	185.00
2	575		As in item no. 574 above but for flush pointing deduct form item 574		Sqm.	(-)20.00
3	576		As in item no. 574 and 575 above but for flush deduct form item 574 and 575.		Sqm.	(-)23.00
4	577		Raised pointing with cement and fine sand of 1.25 F.M. mortar on brick works in proportion of 1:2, including supply of all materials labour and T&P etc. required for proper completion of the work		Sqm.	152.00
5	578		Struck cement pointing 1:2 with colouring materials to match the brick work colour including supply of all materials, labour and T & P etc. required for proper completion of the work. Racking and washing surface.		Sqm.	140.00
6	580		Plaster 12mm. Thick plaster with cement mortar in proportion of 1:2 cement & fine sand of 1.25 F.M.		Sqm.	161.00
7	581		As in item 580 above but with cement mortar in proportion of 1:2 consisting one part cement and two parts of approved coarse sand.		Sqm.	192.00
8	582		As in item 580 above but with cement and fine sand of 1.25 F.M. mortar in 1:3.		Sqm.	139.00
9	583		As in item 580 above but with cement and approved coarse sand in 1:3.		Sqm.	156.00
10	584		As in item 580 above but with cement and fine sand of 1.25 F.M. mortar in 1:4.		Sqm.	126.00
11	586		As in item 580 above but with cement and fine sand of 1.25 F.M. mortar in 1:6.		Sqm.	111.00
12	587		Add for extra labour to all items of plaster if done in ceiling.		Sqm.	11.00
13	597		2 cm (3/4") thick cement plaster in dedo or skirting in 1:2 consisting of one part of cement and 2 parts of approved coarse sand laid in panels, finished with 3 mm (1/8") floating coat of neat cement or cement and marble dust in ratio of 5:1 including supply of all materials, labour and T&P etc. required for proper completion of the work.		Sqm.	216.00
14	598		Engraving lines in the plaster of outer face well vertically and horizontally to display the surface as stone facing as directed by the Engineer-in-charge including labour & T&P etc. required for proper completion of the work. Add for extra labour to all items of plaster.		Sqm.	21.20

(Gyan Prakash Pandey)
 Superintending Engineer
 Azamgarh Circle, P.W.D.,
 Azamgarh