

**CHAPTER-13
PLASTER AND POINTING**

S.No.	SCH. P.W.D	ITEM NO NBO	Description of Work	P.W.D SPEC. NO.	UNIT	LABOUR RATE	OVER ALL RATE
1	2	3	4	5	6	7	8
			Pointing				
1	574		Struck pointing with but with cement mortar consisting of one part cement & two parts of fine sand of 1.25 F.M. including supply of all materials, labour and T&P ect. Required for proper completion of the work.		Sqm		185.00
2	575		As in item no. 574 above but for flush pointing deduct form item 574..		Sqm		(-)20.00
3	576		As in item no. 574 and 575 above but in floor deduct form item 574 and 575.		Sqm		(-)24.00
			Plaster				
4	584		15mm. Thick plaster with 1:4 cement and coarse sand mortar in plinth both side of brick work inner side 15 cm below plinth and out side 15 cm below gound level including supply of all materials, labour and T&P etc. required for proper completion of the work.		Sqm		160.00
5	586		As in item 584 above but with cement and fine sand of FM 1.25 mortar in 1:6 but 12mm thick		Sqm		120.00
6	587		Add for extra labour to all items of plaster if done in ceiling.		Sqm		13.00
7	596		Add extra labour and materials for plaster over rough face of one brick walls.		Sqm		13.00
8	597		2 cm (3/4") thick cement plaster in dedo or skirting in 1:2 consisting of one part of cement and 2 parts of approved coarse sand laid in panels, finished with 3 mm (1/8") floating coat of neat cement or cement and marble dust in ratio of 5:1 including supply of all materials, labour and T&P etc. required for proper completion of the work.		Sqm		218.00

S.No.	SCH. P.W.D	ITEM NO NBO	Description of Work	P.W.D SPEC. NO.	UNIT	LABOUR RATE	OVER ALL RATE
1	2	3	4	5	6	7	8
9	598		Engraving lines in the plaster of outer face well vertically and horizontally to display the surface as stone facing as directed by the Engineer-in-charge including labour & T&P etc. required for proper completion of the work. Add for extra labour to all items of plaster.		R.M		22.00
10	599		Providing and fixing water proofing materials in cement mortar for plastering or in concrete work in the proportion recommended by the Manufacturer.		Sqm	-	30.00